# The pictures have merely explanatory purposes and can be changed with no warning

# **SPIN**

## Automatic A/C and HVAC Systems washing machine (with printer)


- EASY FLUSH PRO automatically performs several recirculating washing steps (direct and reverse) with final recovery and drying
- 5,5 lt/min flow pump, 20lt tank
- A: Interactive multi-language software. Available languages: IT/EN/HR/CZ/DK/D/F/PL/PT/RO/RU/SK/SL/ES/SW/HU
- · Quality control of the washing product through a glass flow meter
- · Final data printing
- · Reusable sintered filter
- Rear connection to dried compressed air or nitrogen (Max 5bar inlet)
- · 230V AC power supply
- Dimensions: 59x46,5x100 cm, Weight: 45Kg
- A: 10 Lt Alpha Flush (washing liquid) included (for orders: cod. 01.000.251, Alpha Flush, 10 lt)
- B: Selection of included adapters (for A/C and refrigeration systems)

### STANDARD ACCESSORIES

### Cod. 01.000.251

10 Lt Alpha Flush (washing liquid)







OPTIONAL

Cod. 01.000.188

**Kit Nitrogen-Hydrogen N<sub>2</sub>H<sub>2</sub> Cylinder (95%/5%)** 950cc, with pressure reducer

# Easy Flush Pro

### **EASY FLUSH PRO**

Cod. 01.000.250



MADE IN ITALY





MADE IN ITALY

### **TECHNICAL FEATURES**

- Flushing liquid tank, 20 lt
- · Coupling for external nitrogen bottle
- · Flexible hoses, 3 mt
- Wheeled
- Voltage: 230 V 50/60 Hz
- Dimensions: 300x375x680 mm
- Weight: 19 kg

### OPTIONAL

Cod. 01.000.91

A/C Flushing liquid for Easy Flush (01.000.171S),10 lt



### **EASY FLUSH**

Cod. 01.000.171S



### Standard accessories:

- A: 1/4 sae, 3/8 sae, 1/2 sae couplings
- . B: Kit of clamps and cone adapters for connection on hoses
- C: New sintered reusable filter
  - D: Flow meter