



STANDARD SERVICE

Start Line TF 311 | 400/3/50 | RAL7016

The entry solution: efficient, fast, good | 9-20" outside rim diameter | 1 Speed

Article number: 1 694 400 024

Description

Perfect for workshops with low to medium volume. Quick and efficient.

- Easy tilt-back pole
- Self-centering four-jaw turntable for precising clamping of the wheel
- Plastic protection on the mounting tool for safe clamping of alloy wheels
- Easy and quick use of pedals - Tilting of mounting arm - Opening and closing jaws of turntable - Control of bead breaker arm - Turning of turntable
- Integrated bead breaker with smooth movement
- Mechanical lock of mounting tool

Optional: For changing runflat tyres (RFT) the TF311 can be extended by an assistance arm (1695903411)

Scope of delivery:

- Inflation gun with pressure gauge
- Mounting lever

Color: RAL7016

Technical Data

Tyre width max.	320 mm
Max. wheel diameter	1050 mm
Compressed air connection	8 - 10 bar
Weight	262 kg
Max. wheel width	13 "
Power supply voltage (AC)	400 V
Power supply frequency	50 Hz
Depth	1120 mm
Height	1710 mm
Width	1050 mm
Rotation speed	6,5 rpm
Packaging length	1150 mm
Packaging width	970 mm
Packaging height	1070 mm
Gross weight	292 kg
Phases	3
Number of mounting speeds	1
Min. inner clamping range	11 "
Max. inner clamping range	22 "
Min. outer clamping range	9 "
Max. outer clamping range	20 "

Accessories

1 695 903 411	Assistance arm TCE 60 for Start Line TF 311 series
1 695 107 492	Plastic protection kit Start Line TF311 series 10 pcs.
1 695 107 493	Bead pressing device for Start Line TF 311 series
1 695 107 496	Motorcycle demounting head for Start Line TF 311 series
1 695 107 494	Bead blaster for Start Line TF 311 series
1 695 107 498	Quick change adapter for mounting head for Start Line TF311 series
1 695 107 501	Rollerboard for Start Line TF 311 series
1 695 107 495	Motorcycle adapter for clamping jaws for Start Line TF 311 series
1 695 107 497	Small lever for Start Line TF 311 series