



STANDARD SERVICE

Start Line BA 201 | RAL7016 | 230V

Easy, quick, efficient: Start Line BA 201 with LED-display and internal measuring arm | Easy Fit | RAL7016

Article number: 1 694 400 026

Description

Easy, quick, efficient: Start Line BA 201 with LED-display and internal measuring arm | Easy Fit | RAL7016

5 different balancing programs:

- DYN: Dynamic clip weights, on both sides of the rim. For balancing of steel rims.
- STA: Choose static balancing if no balancing weights are fitted to both sides of a wheel or to the wheel(s) on a motorbike.
- ALU1: Balancing of light alloy rims by attaching adhesive balance weights to the inner and outer side of a rim.
- ALU2: Attach clip-on balance weights and adhesive balance weights to inside of rim.
- ALUS: Adhesive balance weights for any location on inside of rim

Rim distance, rim diameter, and rim width need to be measured manually.

Scope of delivery:

- Large flange
- 4 cones
- Spacer plate
- Quick clamping nut
- Weight pliers
- Spring
- Weights 100g
- Rim width caliper
- Adhesive weights remover

Color: RAL7016

Technical Data

Max. wheel diameter	800 mm
Weight	123 kg
Measuring time	8 s
Max. rim width	16 "
Max. rim diameter	24 "
Max. wheel width	20 "
Max. wheel weight	65 kg
Depth	885 mm
Height	1085 mm
Electrical connection	230 V / 50 - 60 Hz
Width	705 mm
Min. rim diameter	12 "
Packaging length	1000 mm
Packaging width	760 mm
Packaging height	1170 mm
Gross weight	153 kg

Phases	1
Min. rim width	1,5 "

Accessories

1 695 600 479	Motorcycle Adapter for BA 201
1 695 600 480	Universal Adapter for BA 201
1 695 600 481	Universal Adapter for BA 201