IMMO 801

IMMO 801

Automotive Key & IMMO Programming Tool

IMMO 801 is a professional automotive key & IMMO programming tool that integrates vehicle detection, common maintenance functions, remote control matching, key matching, anti-theft ECU matching, ECU reset, chip reading and writing, and car computer reading and writing. It is suitable for the automotive electronics industry, locksmiths, repair shops and other professional users.

Anti-Theft Matching

Anti-Theft Programming

Vehicle Inspection

26 Common Maintenance Functions

Features

1. The perfect combination of detection equipment and anti-theft programmer, one machine with multiple functions, high cost performance;
2. Support the anti-theft matching function of many models in Asia, Europe, America and China, and more brands will continue to be launched;
3. Support 26 common maintenance functions;
4. Pop-up VCI connector compartment design, the connector is not easy to lose.

Functions

1. Anti-theft matching: support learning, reset, matching, replacement and programming of IMMO, PEPS, EMS, ESCL and other control units;

2. Anti-theft programmer: support anti-theft chip reading and writing, anti-theft ECU reading and writing, key matching and remote control matching and other functions;

3. Vehicle detection: support for code reading, code clearing, data stream reading, action testing, special functions and other full-system and full-function detections;

4. Maintenance function: support 26 common maintenance functions, such as maintenance light reset, throttle matching, brake pad replacement, steering angle reset, anti-theft matching, ABS bleeding injector coding, DPF regeneration, sunroof initialization, Gearbox matching, etc;

5. Test report: Support the display of fault detection, data flow and other reports;

6. Software upgrade: Support online upgrades, including model software, firmware software, and APP software.

Parameters

CPU	4 Core 1.8GHz		Resolution	1280×800
System	Android		Camera	8MP
Memory	4GB		Wi-Fi	2.4GHz/5GHz
Storage	64GB		Working Temperature	0~45℃
Display	8 inch		Storage Temperature	-10~60℃